

Zenith



versione/version:01/2018

BATTERIA SIGILLATA AGM
AGM MAINTENANCE FREE BATTERY

ZGL120042

CHARACTERISTIC / CARATTERISTICHE		
Volt	12V	
Capacity / Capacità	20h	26Ah
	5h	24Ah
Internal Resistance	Full Charged Battery 25°C ≤12mΩ	
Capacity affected by Temperature / Effetti delle temperature sulla capacità	40°C	102%
	25°C	100%
	0°C	85%
	-15°	65%
Self-Discharge 25°C Capacity / Autoscarica a 25°C	after 3 month storage	90%
	after 6 month storage	80%
	after 12 month storage	62%
Charge (Costant Voltage 25°C)	Float	Volt 13.6 - 13.8V
	Charge	Max.9.6Amp. 14.4 - 15 Volt

CHARACTERISTIC / CARATTERISTICHE			
Battery dimensions / Dimensioni batteria			
L/L	W/P	H/A	Tot - H/A
165	176	125	125
Box Dimensions / Dimensioni scatola			
L/L	W/P	H/A	
-	-	-	
Weight / Peso			8.20Kg
Terminal / Terminali			M6
Case / Contenitore			ABS

Amp. (25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	95.0	64.0	48.0	28.5		16.0		6.74	4.47		2.52	1.24
1.65V	90.1	60.9	45.9	27.4		15.4		6.53	4.36		2.47	1.23
1.70V	84.9	57.8	43.7	26.2		14.8		6.30	4.24		2.42	1.22
1.75V	79.7	54.5	41.1	24.9		14.2		6.05	4.10		2.37	1.20
1.80V	74.3	51.3	39.1	23.6		13.5		5.78	3.95		2.31	1.18

Watts (25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	185	121	90.0	55.0	40.0	31.7	19.6	13.4	8.54			
1.65V	173	114	85.1	52.3	38.2	30.3	19.0	13.1	8.39			
1.70V	161	107	80.2	49.4	36.3	28.9	18.3	12.5	8.22			
1.75V	151	99.7	75.2	46.6	34.3	27.5	17.6	12.0	8.03			
1.80V	139	92.7	70.3	43.7	32.3	26.0	16.9	11.4	7.83			


This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact U.B.S. UNION BATTERY SERVICE for the latest information.

Le informazioni contenute in questa scheda tecnica sono solo descrittive e indicative, non sono una garanzia. U.B.S. UNION BATTERY SERVICE si riserva il diritto di aggiornarle/modificarle senza preavviso.




www.unionbatteryservice.it

ZGL120042




Charging characteristics


Charging voltage: $6.90 \pm 0.1V/\text{piece}$ at 25°C



Discharge characteristics (25°C)



Temperature effect on battery self-discharge



Temperature effect on capacity

